


WES3000

TECHNICAL SPECIFICATIONS



Q-FIN

Quality Finishing Machines

General	Unit	WES3000
Authentication		CE-approved
Weight without water	kg	335 kg
Water content	l	300 l
Water use	l/u	4 l/h
Dimensions L x B x H	mm	1645 x 1090 x 2300 mm
Fan	kW	3 kW
Capacity	m ³ /h	3000 m ³ /h
Extraction speed	m/s	19 m/s
Noise	dBA	65 dBA
Control of exhaust installation		Control by power switch or external machine
Standard		
		LED indicator: blue for in operation, red for filling
		Mechanical floating system, automatic filling and levelling
		Fully manufactured in stainless steel
		5 collectors (for easy cleaning)
		Exhaust with silencer
		2" Spillway front
Operation		
Motor		Ventilator 3 kW
Filter		Labyrinth + deflection grid
Consumption		Tap water
Water inlet connection	inch	¾" or ½" GARDENA-Fitting
Air inlet connection	mm	Ø 200 mm
Electrical specifications		
Input Voltage	V	400 V (3L+N+PE)
Frequency	Hz	50 Hz
Input Current	A	8 A
Connected load	kW	4 kW
400V plug	A	400 V CEE plug / 16 A / 5 pins